

QUOTE REQUEST FORM

This form is the first step to creating your customized Bally Walk-In Cooler/Freezer with up to 3 compartments. (If your Walk-In requires more than 3 compartments, you do not need to fill out the form just email us or call 1-800-24BALLY.) Please fill out this form, adding any comments or questions, and email it to sales@ballyrefboxes.com.

A Bally representative will contact you with information and help you find a dealer in your area.

Name:		Email:				
Business Name:		Project Name:				
Address:		City:	State	Zip		
Phone:		Fax:				
OVERALL DIMENSIONS of WALK-IN 4" Panel 5" Panel 6" Panel						
Estimated LENGTH:	Estimated WIDTH:		Estimated HEIGHT:			
15'5", 16'4½", 17'4", 18'3½", 19'3", 20'2½". Longer buildings are available in additional 5¾" increments.	4", 8'8½", 9'2¼", 9'8", 10'1¾", 10'7½", 11'1¼", 7'9", 8'2¾", 8'8½", 9'2¼", 9'8", 10'7", 12'0¾", 12'6½", 13'0¼", 13'6", 14'5½", 10'7½", 11'1¼", 11'7", 12'0¾", 12'0¾", 13'6", 14'5½". Longer buildings are available in additional 5¾" ings are available in additional increments.		(Single length verticals) Taller buildings are available in additional 12" increments, with stacked vertical pan-			
*Non-Standard dimensions can expect longer lead times.						
Number of Compartments? (Check one)	e or Depression anding Existing Building ate:	Height of Building (if against one): ———— Number of Walls Sizex				
Dimensions: Cooler: LxWxH Freezer: LxWxH Comments:						
Exterior Finish: (Check one) Stucco-embossed Galvalume steel Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White aluminum Stucco-embossed Sand-tan galvanized steel Stucco-embossed White galvanized steel Sandex Stone-textured Galvanized steel Embossed Stainless		☐ Stucco-em ☐ Smooth W ☐ Stainless st ☐ Stucco-em ☐ Stucco-em ☐ Stucco-em ☐ Smooth W	Interior Finish: (Check one) Stucco-embossed Galvalume steel Smooth White galvanized steel Stainless steel Stucco-embossed aluminum Stucco-embossed White aluminum Stucco-embossed White galvanized steel Smooth White aluminum Embossed Stainless			

FLOORS	Floor Types: (Check one) Less Floor w/ Floor Light Use—Foot Traffic Medium Use—Hand Truck or Small Cart Heavy Duty—Structurally Reinforced (Keg or Pallet Jack & Queen Mary)		Floor Panel Finishes: (Check one) 3/16" Aluminum Diamond Tread Overlay 100 ga. Smooth Aluminum 16 ga. Stainless Steel Rigidized Aluminum Diamond Pattern 1/8" Aluminum Diamond Tread Rigidized Stainless Steel Diamond Pattern 16 ga. Galvanized Steel (Non NSF - to be used under any NSF approved Overlay) Extra Overlay: 3/16" Diamond Tread		
			S - Options: (Check of ne roof w/ tapered insu	<i>ne)</i> ulation	
	No. of Doors: Width: Choose from: 30", 36", 42", 48", 54", 60"	Height: Choose from: 66", 78", 84"		Observation Window in Entrance Door: 14" x 14" Deadbolt Handle Latch: (K27C)	
OOORS	Width: I Choose from: 30", 36", 42", 48", 54", 60"	Height: Choose from: 66", 78", 84"		Super Doors (1/8" Diamondtread kickplate on both sides, 3 rd hinge. Standard Sizes; included unless noted)	
	Width: Choose from: 30", 36", 42", 48", 54", 60"	Height: Choose from: 66", 78", 84"		Glass Display Doors: Number of Doors: Size:x	
	Additional Doors:			☐ Sliding Door: Qty Size:x Slide Direction: ☐ Left ☐ Right	
		ACCE	SSORIES		
☐ Pressure Relief Port (required for freezers) Additiona ☐ Partition Walls (location) ☐ Yes ☐ Free Standing Shelving If yes: ☐		Lighting: No 4' LED Other	Alarm Systems: Modularm 75L C WEISS Other: Please specify		
	REFRIGERATION	ON SYS	TEMS Sto	orage Only Product Load	
Condensing Unit: Indoor Remote Outdoor Air-Cooled Remote Self-Contained (PT-Unit) Cooder Condens Condens		n (Choose one): er	Application (Choose one): Cooler Freezer Condensing Unit: Indoor Remote Outdoor Air-Cooled Remote Self-Contained (PT-Unit) Indoor Water Cooled		

Notes: For line sets ≤ 75'

SmartVap+ Evaporator Controls are Standard at Bally.